


DURATRUSS - DT 33

Spezifikationen

Hauptrohr	50 x 2 mm
Verbindungsrohre	20 x 2 mm
Aluminium	EN-AW 6082 T6 (AlMgSi)




Belastungstabelle DT 33	1m	1,5m	2m	3m	4m	5m	6m	8m	10m	12m
Punktbelastung (kg)	725	660	600	490	415	350	270	205	160	135
Durchbiegung (mm)	1,6	2,2	2,9	5,8	10,5	16,5	16,8	33,4	50,8	81,3
Verteilte Belastung (kg/m)	1300	1010	750	396	195	133	98	56	35	23
Durchbiegung (mm)	2,1	3,1	4,8	7,4	12,6	24	29	52,5	82,2	115,2

DURATRUSS - DT 34

Spezifikationen

Hauptrohr	50 x 2 mm
Verbindungsrohre	20 x 2 mm
Aluminium	EN-AW 6082 T6 (AlMgSi)



Belastungstabelle DT 34	1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m
Punktbelastung (kg)	2400	2080	1340	1000	840	680	600	500	460	400	360	320
Durchbiegung (mm)	2,3	5,3	11	13,3	20,5	28	38,7	47,7	62,5	74,4	89,8	104,5
Verteilte Belastung (kg/m)	2400	1304	800	438	288	194	149	116	90	70	58	50
Durchbiegung (mm)	2,3	5,4	8,7	16,2	23,9	33,9	46,5	58,2	72,3	88	105,5	126,1